NewLook International, Inc. Mean Klean™

Technical Information Sheet



NewLook Mean Klean™ is a liquid chemical that dissolves concrete and mortar for easier cleaning. It is the eco-friendly, non-fuming alternative to harsh cleaning acids or hazardous etching chemicals. The advanced liquid formula dissolves and physically breaks down concrete by attacking the Portland cement and other unique chemical properties, reducing it to a mush that's easy to clean and remove from the surface.

USES AND BENEFITS

- Use Mean Klean to safely clean, dissolve and remove concrete, cured cement, mortar, grout and stucco.
- Use to clean trowels, screeds, hand tools, mixers, pumps, scaffolds, mud tubs, mud boards, trucks, trailers and silos, saws, drills, generators, augers and more.
- May be used to etch concrete and open the surface pores in preparation for decorative coatings.

APPLICATION PREREQUISITES

- Mean Klean is water-neutralized. Never wet surface with water before applying Mean Klean
- Protect walls and adjacent areas where dissolving is not desired
- DO NOT dilute Mean Klean.

APPLICATION OF MEAN KLEAN

- 1. Mean Klean is intended to be used as provided and NOT diluted.
- Apply with a NewLook Applicator Brush[™] or Sprayer. Some tools may be soaked in travs.
- Completely saturate concrete with Mean Klean. Surface will turn white, then darken. White residue may appear if Mean Klean evaporates.
- Do not rinse. RE-apply to reactivate as needed until concrete has softened and dissolved.
- 5. Allow Mean Klean to penetrate 10-15 minutes. Keep surface saturated.
- Concrete will soften and release from surface after approximately 20-30 minutes. Needed soak time depends on the thickness of material being removed.

- Rinse with cold water. Use a garden hose with nozzle or pressure washer.
- 8. Repeat as needed.
- 9. Mean Klean will not harm paint, metal or wood. Only Portland Cement.
- Mean Klean may also be used for concrete etching. Apply with a wand sprayer evenly. When etch time has completed, neutralize with water. A mop may be necessary to clean up the residue.

STORAGE

- Store in original container in areas inaccessible to children and pets.
- Keep containers tightly sealed.
- Do not reuse empty container. Rinse empty container and replace cap before discarding.
- DO NOT allow product to freeze.

LIMITATIONS

- Any water on the material will neutralize the effects of Mean Klean and it will no longer be effective.
- Avoid prolonged contact with concrete surfaces that should not be dissolved.

CAUTION

KEEP AWAY FROM CHILDREN AND ANIMALS. Before using or handling, read the MSDS and Product Instructions. DO NOT CONSUME. Avoid contact with eyes and skin. Wear rubber gloves, aprons and safety eye goggles. Use good hygiene when handling this product. It is recommended that you wash and bathe after each use.

PACKAGING AND COVERAGE

Туре	Container Size
Mean Klean	22 Oz Spray
	1 Gallon or 2.5 Gallon

WARRANTY

NewLook International, Inc. Mean Klean ("Product") are intended for use by licensed contractors and other installers, experienced and trained in the use of these products. Product is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of Product, therefore no other oral or written representation or statement of any kind, express or implied, now or hereafter made is authorized or warranted by NewLook International, Inc. or its affiliates, and NewLook International, Inc. and its affiliates hereby disclaims all such warranties, including those of merchantability or fitness for a particular purpose. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. NewLook International, Inc. shall not be liable for special, incidental, or consequential damages, including delays or lost profits. Communication of this warranty and its limitations to end users is not the responsibility of NewLook International, Inc. but should be communicated by those in direct contact with the end user. Any claim regarding product defect must be received in written notice or after the specified time interval. The end user shall be responsible for determining Product's suitability and assumes all risks and liability.