NewLook International, Inc. NanoSet Protector™

Technical Information Sheet



NewLook NanoSet Protector™ is a penetrating sealer and conditioner formulated to enhance and protect polished concrete floors. It is a unique product that includes nano-sized silica particles for increased surface hardness and lithium for water repellency.

USES AND BENEFITS

- Enhances colored concrete floors
- Increases durability and stain resistance of concrete floors
- Increases slip resistance
- Ease of maintenance and cleaning
- · Water based, environmentally friendly product

APPLICATION METHODS

Apply a light mist from a pump sprayer. Using a damp micro fiber or flat cotton pad applicator, spread NanoSet Protector™ in a thin film coating using a "figure 8" motion to reduce streaking and prevent puddling. A second coat should be applied after the first is tack-free. Work leaving a wet edge and work in areas bordered by joints or natural breaks. High speed burnishing using fiber pad (red or black) or hogs hair pad will further enhance the finished surface.

PREPARATION

Complete all floor prep including densification, coloring, and polishing before applying NanoSet Protector. Clean floor to remove dust and debris. The surface should be completely clean and dry before application.

PRECAUTIONS

Cure finished floor for 24 hours before allowing regular foot traffic. Do not allow standing water to remain on the surface for the first 48 hours. Protector is intended for interior use and will not withstand UV exposure. Maintain floor with NewLook's NanoSet Cleaner™.

PACKAGING AND COVERAGE

Product	Bucket Size	Approximate Coverage (Sq Ft.)
NanoSet Protector	1 or 5 Gallon	1,500-2,000 SF Per Diluted Gallon (Dilute 1:1)

WARRANTY

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.

NEWLOOK INTERNATIONAL, INC. PRODUCTS available through: